

**Gulvvarme**

Datablad

# Wavin Sentio Telestat



**wavin**

orbia 

## Anvendelse

Wavin telestat 24V NC kan sammen med Wavin styreenheder anvendes til on/off regulering af f.eks. Wavin 3/4" og 1" gulvvarmefordelerrør.

Generelt	
Driftsspænding	24V AC/DC, +20%... -10%
Maks. start strøm	< 300mA i under 2 min.
Strømförbrug	1W
Vandring	5 mm
Type	NC (Normally Closed)
Lukkekræft	100N ± 5%
Medie temperatur	0 °C – 100 °C
Beskyttelsesklasse	IP 54 / II
CE mærket i henhold til	EN 60730
Tilslutningskabel	2 x 0.75 mm <sup>2</sup>
Længde tilslutningskabel	1,2 m
Overspændingsbeskyttelse i henhold til	EN 60730-1 Min. 2.5 kV



Wavin is part of Orbia, a community of companies working together to tackle some of the world's most complex challenges. We are bound by a common purpose: To Advance Life Around the World.



**Wavin** | Wavinvej 1 | DK-8450 Hammel | Telefon +45 8696 2000 | Internet [www.wavin.dk](http://www.wavin.dk)  
E-mail [wavin.dk@wavin.com](mailto:wavin.dk@wavin.com) | [www.wavin.com](http://www.wavin.com)

© 2025 Wavin Wavin reserves the right to make alterations without prior notice. Due to continuous product development, changes in technical specifications may change. Installation must comply with the installation instructions.