

**Gulvvarme**

Datablad

# Wavin Sentio fortrådet udendørs sensor



**wavin**

orbia 

## Anvendelse

Wavin fortrådet udendørs temperatursensor anvendes sammen med Sentio sytreenheden, hvis fremløbstemperaturen ønskes reguleret.

Generelt	
Strømforsyning	10 V DC - 30 V DC (via intern bus)
Maks. forbrug pr. enhed	1 mA standby 25 mA for kabelvalg
Kontroltemperatur område	50T110 (-50-110°C), nøjagtighed +/- 0,6 °C
Måleområde, temperatur	25T50 (-25-50 °C)
Dimensioner	90 x 110 x 35 mm
Vægt	125 g
Beskyttelsesklasse	IP53 (EN 60529)
Omgivelsestemperatur	Luftfugtighed 0-90%, udendørs, ikke kondenserende
I henhold til	EN 60730-1, EN 55032, EN 55024, EN 50581



Wavin is part of Orbia, a community of companies working together to tackle some of the world's most complex challenges. We are bound by a common purpose: To Advance Life Around the World.



**Wavin** | Wavinvej 1 | DK-8450 Hammel | Telefon +45 8696 2000 | Internet [www.wavin.dk](http://www.wavin.dk)  
E-mail [wavin.dk@wavin.com](mailto:wavin.dk@wavin.com) | [www.wavin.com](http://www.wavin.com)

© 2025 Wavin Wavin reserves the right to make alterations without prior notice. Due to continuous product development, changes in technical specifications may change. Installation must comply with the installation instructions.