

Gulvvarme

Datablad

Wavin Sentio

fortrådet rumtermostat, fortrådet rumsensor



wavin

orbia 

Anvendelse

Wavin Sentio fortrådet rumtermostat/rumsensor anvendes sammen med Wavin Sentio styreenheden til regulering af rumtemperaturen.

Generelt	
Strømforsyning	8 V DC - 30 V DC (via intern bus)
Maks. forbrug pr. enhed	30 mA (ved fuldt oplyst display)
Måleområde, rumtemperatur	T50 (0-50°C), nøjagtighed +/- 0,5 °C, trin 0,1 °C
Måleområde, luft fugtighed	10 - 90% rH, nøjagtighed +/- 3%, trin 1% rH
Dimensioner	62 x 85 x 22 mm
Vægt	55 g
Beskyttelsesklasse	IP 31 (EN 60529)
Omgivelser	T40 (0-40 °C) Indendørs, ikke kondenserende
I henhold til	EN 60730-1, EN 55032, EN 55024, EN 50581



Wavin is part of Orbia, a community of companies working together to tackle some of the world's most complex challenges. We are bound by a common purpose: To Advance Life Around the World.

Wavin | Wavinvej 1 | DK-8450 Hammel | Telefon +45 8696 2000 | Internet www.wavin.dk
E-mail wavin.dk@wavin.com | www.wavin.com

© 2025 Wavin Wavin reserves the right to make alterations without prior notice. Due to continuous product development, changes in technical specifications may change. Installation must comply with the installation instructions.

