



1	EuroREK Omega grease separator (EN1825) NS7 (x) <input type="checkbox"/> Max. flow rate 7 l/s NS10 <input type="checkbox"/> Max. flow rate 10 l/s PE-MD body $\phi 2170$ (ball) temperature endurance max. 50°C	1
	V Total volume	4180 l
	Vg Grease storage capacity	400 l (H=150 mm)
	Vs Sludge storage capacity	1000 l
2	Inlet / Outlet sewer	D160
3	Grease alarm unit	
4	Maintenance shaft D600/1000, material PE-MD Indoor installation model (Under the floor) h = 500-1000 mm (x) <input type="checkbox"/> Separator with solid HUK 600 maintenance shaft Ground installation model, h = 900-1300...2100-2500 mm h = Installation depth of separator from ground surface (mm) h= 900...1300 mm (x) <input type="checkbox"/> h=1300...1700 mm <input type="checkbox"/> h=1700...2100 mm <input type="checkbox"/> h=2100...2500 mm <input type="checkbox"/> h = _____ mm (Max. 2500 mm)	1
5	Ventilation outlet (as needed)	D110
6	Floating adjustable cast iron lid set $\phi 600$ . Standard EN124 Frame for two covers (also for the inner cover) Cover class A15 (1.5 tn) (x) <input type="checkbox"/> Cover class D400 (40 tn) (x) <input type="checkbox"/> Cover class C250 (25 tn) <input type="checkbox"/>	1
<b>ACCESSORIES:</b>		
7	Inner cover (gas proof)	(x) <input type="checkbox"/>
8	Ladder in maintenance shaft, material Al	(x) <input type="checkbox"/>
9	Heating cabel set for maintenance shaft (230V). Effective 150 W MCMK cabel for electricity (230V) connection length 5 m. Including insulation inner cover. Not including frost insulation	(x) <input type="checkbox"/>
10	ACCESSORY: Anchoring belt (Polyester), weight capacity 1000 kg, 4 pcs	(x) <input type="checkbox"/>
11	Anchoring plates package, GRP, 4 pcs	(x) <input type="checkbox"/>
12	Data transfer unit	(x) <input type="checkbox"/>
13	Emptying pipe with flange DN80 (PN10), PVC Degree angle in separator: _____	(x) <input type="checkbox"/>
14	Imubox quick coupling box for 1 pc. DN80 Suction pipes	(x) <input type="checkbox"/>
15	Inspection chamber D200/160	(x) <input type="checkbox"/>
16	Wavin NOK D425/D160 sampling shaft	(x) <input type="checkbox"/>

Title: EuroREK Omega NS7 and NS10 Grease separator (EN1825)		Drawing type CUSTOMER DRAWING	
Design by: HT/JS	Approved by: TaP 22.02.18	Drawing no. 32GB05be	Date: 22.02.2018
Construction site:		Scale:	
			
		WAVIN-LABKO Ltd. VISIOKATU 1 FIN-33720 TAMPERE FINLAND tel. +358 20 1285200 fax. +358 20 1285280	