













# Gummiringe- oversigt

	Glat uPVC trykfløb	Glat uPVC	Glat uPVC	Glat uPVC	M/I uPVC	M/I uPVC
						
<b>Dimension</b>	110-160-200-225-250	110	160-200	250-315-400-500	110	160-200
<b>Gummiring</b>	Power Lock	WaFix	WaCop	PowerLock	WaFix	WaCop
<b>Gummitype</b>	EPDM	TPE*	SBR	EPDM	TPE*	SBR
<b>Ringstivhed</b>	PN6	SN4/SN8	SN4/SN8	SN8	SN4/SN8	SN4/SN8
<b>Godkendelse</b>	NPM	NPM	NPM	NPM	NPM	NPM
<b>Anvendelse</b>	Tryksystem	Gravitation	Gravitation	Gravitation	Gravitation	Gravitation

	Glat PP	Glat PP	Glat M/L PP	Glat M/L PP	WavinRib	X-Stream
						
<b>Dimension</b>	110-160	200	110-160	200	200-250-315-400-500-600	100-150-200-250-300-400-500-600-800
<b>Gummiring</b>	FixLock	WaCop	FixLock	WaCop		
<b>Gummitype</b>	TPE*	SBR	TPE	SBR	EPDM/NBR	EPDM/NBR
<b>Ringstivhed</b>	SN4/SN8	SN4/SN8	SN4/SN8	SN4/SN8	SN8	SN8
<b>Godkendelse</b>	NPM	NPM	NPM	NPM	NPM	NPM
<b>Anvendelse</b>	Gravitation	Gravitation	Gravitation	Gravitation	Gravitation	Gravitation

TPE **Thermoplastic elastomers**    Oliebestandig  
 SBR **Styrene Butadiene Gummi**  
 NBR **Nitril gummi**    Oliebestandig  
 EPDM **Ethylene Propylene Gummi**